

What is claimed is:

1. A media device comprising:

a remote controller producing a remote code for controlling
for its own use, a remote code for controlling peripheral
media devices, and selection signals of external input
sources in accordance with a user's selection;

a communication port to be connected with the peripheral
media devices through a communication line;

a receiver part receiving one of the remote codes from the
remote controller;

a controller verifying that a present external input source
corresponds to which one of the peripheral media devices
and produces a code conversion control signal and an output
control signal;

a memory storing code conversion data; and

a code converter converting the code into a code
corresponding to the verified peripheral media device using
the code conversion data stored in the memory by responding
to the code conversion control signal, the code converter
outputting the converted code to the verified peripheral
media device through the communication port by responding
to the output control signal.

2. The media device of claim 1, wherein the media device and peripheral media devices include TV receiver, DVD, video cassette recorder, and set-top box.

3. The media device of claim 1, wherein the communication port is one of RS232C, I2C, and parallel port.

4. The media device of claim 1, wherein the media device further comprises a display part displaying a menu of the media device's own, a menu of the verified peripheral media device, and an operation status of the controller by responding to the code of the remote controller.

5. The media device of claim 1, wherein the remote controller includes keys for selecting the external input sources corresponding to the peripheral media devices enabling to be connected to the media device.

6. The media device of claim 1, wherein the peripheral media devices includes communication ports identical to the communication port so as to establish communication channels with the media device.

7. A method of operating peripheral media devices using a media device having a remote controller, comprising the steps of:

monitoring whether a remote code is received from a remote controller;

verifying that a present external input source mode corresponds to which one of the peripheral media devices when the remote code is received from the remote controller; and

converting the received code into a code corresponding to the present external input source mode when the peripheral media device corresponding to the present external input source mode is connected to the media device and then transferring the converted code to the peripheral media device corresponding to the present external input source mode.

8. The method of claim 7, further comprising the step of displaying on a screen whether the media device and the peripheral media device corresponding to the present external input source mode are connected to each other.

9. The method of claim 7, further comprising the step of displaying character and video signals from the

peripheral media device corresponding to the present external input source mode on a screen of the media device in accordance with the remote code.

5 10. The method of claim 7, further comprising the steps of: processing the code to operate the media device itself when the peripheral media device corresponding to the present external input source mode fails to be connected to the media device or the present external input source mode corresponds to the media device itself; and
10 operating the media device in accordance with a command corresponding to the processed code.

11. The method of claim 10, wherein information of the code processed by the media device itself includes volume adjustment of the media device and change of the present external input source mode.

12. The method of claim 7, wherein the media device and
20 peripheral media devices include TV receiver, DVD, video cassette recorder, and set-top box.

13. The method of claim 7, further comprising the steps of:

1 executing a command corresponding to the converted code in
the peripheral media device corresponding to the present
external input source mode;

transferring an execution result from the peripheral media
5 device corresponding to the present external input source
mode to the media device; and

displaying an image according to the execution result on a
screen and outputting a voice according to the execution
result through a speaker of the media device.

10
14. The method of claim 7, further comprising the step of
providing a communication channel set-on or set-off
signal from the remote controller to the media device by
a user's selection so as to turning on or off a mode for
establishing communication channels between the media
15 device and the peripheral media devices.

20
15. The method of claim 14, wherein the communication
channel set-on signal is provided when the peripheral
media devices have the same communication ports of the
media device on an on-screen display menu of the media
device from the remote controller by a user and wherein
the communication channel set-off signal is provided
when the peripheral media devices fail to have the same

communication ports of the media device on an on-screen display menu of the media device from the remote controller by a user.

5 16. The method of claim 15, wherein the communication port is one of RS232C, I2C, and parallel port.

17. The method of claim 7, further comprising the steps of:
monitoring whether a code to change the present external input source mode into a new external input source mode is produced from the remote controller; and
relieving the established communication channel between the present external input source and the media device and establishing a new communication channel between the new external input source and the media device.